

Features

- Solid state electronic timer used to automatically control ASCO solenoid valves
- Typically used with ASCO Solenoid Valves for automatic draining of condensate in compressed air systems
- Selectable timing ranges (2-40 seconds "on"; 30 seconds to 45 minutes "off")
- Manual override for test/reset
- LED lights to indicate timing phase

Technical Specifications

| | |
|--------------------------|-----------------------------------|
| Supply Voltage | 24 - 240V AC/DC 50/60 Hz |
| Current Consumption | 4 mA max. |
| Operating Temperature | 14°F - 122°F |
| Environmental Protection | Type 4 |
| Switch Capacity | 1 Amp |
| Inrush Current Capacity | 10 Amps for 10 mSec |
| Duty Cycle | 100% |
| Repeat Accuracy | ± 0.1% |
| Scale Accuracy | ± 10% |
| Reset/Test | Manual Touch Switch |
| Printed Circuit Board | UL 94V0 |
| Connection | DIN 43650 ISO-4400/6952 |
| Indicators | LEDs to indicate phases |
| On Time | Adjustable from 2 to 40 sec. |
| Off Time | Adjustable from 30 sec to 45 min. |



Timer and Accessories Kit Numbers

| | |
|---|----------------------------|
| Timer Catalog Number: | 272839-001 272839-009** |
| Power Cord* Kit Number: | 272852 |
| DIN Connector Kit Number: | 272873 |
| * 6' power cord has DIN connector and 3-prong plug for wall outlet. ** For use with DIN 11 CDV Assemblies. | |

Dimensions inches (mm)

